

Direct Water Cooling Type

BWD Series

BUILT ON TRUST

BWD Series Direct Water Cooling Type Specification

Model	Motor Power		Flow Meter	Pressure	Lub Oil	Outlet Diameter	Dimension	Weight
	(kW)	(HP)	(m^3/ min)	(bar)	(ℓ)		L x W x H (mm)	(Kg)
BWD 55	55	75	10.3	7	30	G2 "	2100 x 1300 x 1580	1900
			9.6	8				
			8.7	10				
			7.5	13				
BWD 75	75	100	13.5	7	35			2000
			12.5	8				
			11.2	10				
			10.0	13				
BWD 90	90	125	16.3	7	40	DN50	2200 x 1300 x 1580	2050

Model	Motor Power		Flow Meter	Pressure	Lub Oil	Outlet Diameter	Dimension	Weight
	(kW)	(HP)	(m³/ min)	(bar)	(ℓ)		L x W x H (mm)	(Kg)
			15.9	8				
			14.0	10				
			12.2	13				
BWD 110	110	150	21.0	7	50	DN65	2650 x 1700 x 1750	3400
			20.0	8				
			17.0	10				
			14.8	13				
BWD 132	132	180	23.5	7				
			22.5	8				
			21.0	10				
			18.0	13				
BWD 160	160	220	28.0	7	60	DN80	2800 x 1700 x 1750	4000
			28.5	8				
			24.5	10				
			20.3	13				
BWD 185	185	250	32.0	7				
			30.0	8				
			27.8	10				
			24.5	13				
BWD 200	200	280	34.3	7				
			32.9	8				
			30.2	10				

Model	Motor Power		Flow Meter	Pressure	Lub Oil	Outlet Diameter	Dimension	Weight
	(kW)	(HP)	(m^3/ min)	(bar)	(ℓ)		L x W x H (mm)	(Kg)
			27.2	13				
BWD 220	220	300	36.0	7	100	DN100	3200 x 1980 x 1950	4900
			34.2	8				
			30.2	10				
			27.8	13				
BWD 250	250	340	43.5	7				
			41.8	8				
			38.0	10				
			34.5	13				
BWD 315	315	425	57.6	7	220	DN125	4200 x 2250 x 1950	6000
			54.5	8				
			50.0	10				
			43.4	13				
BWD 355	355	480	64.5	7			4290 x 2250 x 1950	6200
			62.5	8				
			56.0	10				
			48.6	13				
BWD 560	560	750	100.0	8	440	DN200	3416 x 2288 x 2172	9200
			86.0	10				

Note:

1.Air pressure: Min 0.5Mpa, Max 1.5 Mpa. Selected Voltage Range: 3KV, 6KV,1.0KV

2.The above values can be altered for improvements without any notice to customer.

BUMA CE CO.,LTD.
BUMA Construction Equipment

BUILT ON TRUST

505DUKAM-RI, JUCHON-MYON, GIMHAE-CITY, GYEONGNAM, KOREA (Zip Code: 621-843)

TEL: +82-55-337-9891-3

FAX: + 82-55-337-9894

Email: jack@bumace.com

Website: www.bumatec.co.kr