


2:1ELIP.HEAD(t8)
Afterformingmin.TH'K:7.6







NOZZLE ORIENTATION




SEAMPLAN




SHELLTO HEAD




SHELLTO SHELL




MANHOLE DETAIL



LIFTINGLUG



BASE&PILLAR



SPECIFICATION

1. Catpacity:2000litres
2. Design pressure : 10 kg/cm²
3. Working pressure : 08 kg/cm²
4. Hydro test pressure : 15 kg/cm²
5. VietNamstandardcode:TCVN8366:2010

Capacity			2.028 m³	
WEIGHT&CAPACITY(Estimated)				
M1	1	150x190	MANHOLE	
N5	1	15A	DRAIN	
N4	1	20A	SAFETY VALVE	
N3	1	10A	PRESSUREGAUGE	
N2	1	50A	AIROUTLET	
N1	1	50A	AIRINLET	
MARK NO	NO. REQ	SIZE	DESIGNATION	REMARKS

MARK	DESCRIPTION	DIMENSION	MATERIAL	QUANTITY	REMARKS
9	GussetPlate	t5X50	CT3	2	
8	Buffer	t5	SyntheticRubber	1	
7	GussetPlate				
6	AnchorBoltNut	M20	SS400	3SETS	
5	LiftingLug	t10	CT3	2	
4	BasePlate	t8	SS400	3	
3	Chassis	U300X90	CT3	3	
2	Head	t8	SS400	2	2:1ELLIP
1	Shell	t8	SS400	1	

FUNCTION	NAME	SIGN
DESIGNER	Ng.ThanhTuan	
DRAWER	Ng.ThanhTuan	
CHECK	*DoQuocDung*	
DATE	SCALE	
042011	1:20	
	REVISION	

INVESTOR

TITLE **AIRRECEIVERTANK**

DESCRIPTION **ASSEMBLY&DETAILDWG.**

DRAWINGNO.